

ADIN1512

Adler DIN 12V 15W



- Features:
- Can be installed on DIN Rail TS-35
 - Universal AC input voltage range
 - Cooling by free air convection
 - Isolation class II
 - Protections: Short circuit / Overload / Over voltage / Over temperature



ELECTRICAL SPECIFICATION

Product Type	DIN Rail Power Supply, Industrial Power Supply, Power supply
Output Voltage	12V DC
Rated Current	1.25 A
Power (W)	15 W
Dimming	No
AC input voltage range	Universal
PFC	No
Protection class	II
AC Current (typ.)	0.11 A
Inrush Current (typ.)	65A @ 240VAC Full Load
IP protection level	IP20
Working Temperature range	-20°C ÷ +60° C
Working Humidity range	5% ÷ 95% RH non-condensing
Storage Temperature and Humidity	-40°C ÷ +70°C, 5 ÷ 95% RH non-condensing
Safety Standards	EN IEC 62368-1:2024+A11:2024
Withstand Voltage	IN/OUT: 1500VAC / 10mA, 60s
EMC Emission	EN 55032:2015+A1:2020+A11:2020
EMC Immunity	EN 55035:2017 + A11:2020

Harmonic Current	EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A2:2021/AC:2022-1
Dimmensions (L x W x H)	18x92.5x58.5 mm
Weight (kg)	0.075
Packing	100 pcs/box
Warranty	2 years
Mounting	DIN

MECHANICAL SPECIFICATION

